

Appl. No. 10/028,140
Amendment and/or Response
Reply to Office action of 29 March 2004

Page 2 of 7

Listing of Claims:

A listing of the entire set of pending claims (including amendments to the claims, if any) is submitted herewith per 37 CFR 1.121. This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Previously presented) A solid state multi-spectral light source comprising:
a plurality of light-emitting diodes,
wherein:
at least two of the light-emitting diodes produce two different colors, and
the light source is configured to produce at least two different color light bars
that scroll through selective activation of like colored light-emitting diodes in
dependence upon an image signal.
2. (Original) The light source according to claim 1, wherein the light-emitting diodes
are arranged in groups, each group having at least two light-emitting diodes which
produce the two different colors.
3. (Original) The light source according to claim 2, wherein the light-emitting diode
groups each include three light-emitting diodes which produce three different colors.
4. (Cancelled)
5. (Original) The light source according to claim 1, wherein
the light-emitting diodes are defined on a wafer.
6. (Original) The light source according to claim 1, wherein
the light-emitting diodes are formed by a plurality of substrates disposed on a
circuit board,
each of the light-emitting diodes corresponding to one of the plurality of
substrates.

Appl. No. 10/028,140
Amendment and/or Response
Reply to Office action of 29 March 2004

Page 3 of 7

7. (Previously presented) A multi-spectral light source system comprising:
a light valve; and
a solid state multi-spectral light source that flashes different colored light bars onto the light valve to produce a color image, the light source including a plurality of light-emitting diodes, wherein at least two of the light-emitting diodes produce two different colors.
8. (Original) The light source system according to claim 7, wherein the light-emitting diodes of the light source are arranged in groups, each group having at least two light-emitting diodes which produce the two different colors.
9. (Original) The light source system according to claim 8, wherein the light-emitting diode groups of the light source each include three light-emitting diodes which produce three different colors.
10. (Previously presented) The light source system according to claim 8, wherein the light-emitting diode groups of the light source produce two different color light bars that flash through selective actuation of like colored light-emitting diodes in accordance with an image signal.
11. (Original) The light source system according to claim 7, wherein the light-emitting diodes of the light source are defined on a wafer.
12. (Original) The light source system according to claim 7, wherein the light-emitting diodes of the light source are defined by a plurality of substrates disposed on a circuit board, each of the light-emitting diodes corresponding to one of the plurality of substrates.

Appl. No. 10/028,140
Amendment and/or Response
Reply to Office action of 29 March 2004

Page 4 of 7

13. (Previously presented) A method of producing multi-spectral light, the method comprising:

providing plurality of light-emitting diodes;

selectively activating subsets of the plurality of light-emitting diodes to produce color light bars of at least two different colors in dependence upon an image signal.

14. (Original) The method according to claim 13, wherein the providing step includes arranging the light-emitting diodes in groups each having at least two light-emitting diodes producing the two different colors.

15-16. (Cancelled)

17. (Previously presented) A multi-spectral light source system comprising:

a light valve; and

a solid state multi-spectral light source that scrolls different colored light bars onto the light valve to produce a color image, the light source including a plurality of light-emitting diodes, wherein at least two of the light-emitting diodes produce two different colors.

18. (Previously presented) The light source system according to claim 17, wherein the light-emitting diodes of the light source are arranged in groups, each group having at least two light-emitting diodes which produce the two different colors.

19. (Previously presented) The light source system according to claim 18, wherein the light-emitting diode groups of the light source each include three light-emitting diodes which produce three different colors.

Appl. No. 10/028,140
Amendment and/or Response
Reply to Office action of 29 March 2004

Page 5 17

20. (Previously presented) The light source system according to claim 18, wherein the light-emitting diode groups of the light source produce two different color light bars that scroll through selective actuation of like colored light-emitting diodes.

21. (Previously presented) The light source system according to claim 17, wherein the light-emitting diodes of the light source are defined on a wafer.

22. (Previously presented) The light source system according to claim 17, wherein the light-emitting diodes of the light source are defined by a plurality of substrates disposed on a circuit board, each of the light-emitting diodes corresponding to one of the plurality of substrates.